

Superior KeyPad Fibra

Wired keypad with touch buttons

This is a device of the Superior product line. Only accredited Ajax Systems partners can sell, install, and maintain Superior products.




*** Management with codes

- Four types of access codes: general, for registered users, for unregistered users, for RRU
- Remote code and access rights management in Ajax apps



Sabotage protection


- Passcode guessing protection
- Duress codes to simulate system disarming and activate a silent alarm
- Tamper alarm
- Built-in panic button



Additional features


- Support for automation scenarios: by arming/disarming, by pressing panic button
- Ability to mute interconnected fire detector alarms

- Security mode indication
- Minimalist design with two color options to suit any interior




Fibra communication technology

- Up to 2,000 m (6,550 ft) of wired communication range with an Ajax hub¹ or Fibra line extension module
- Encrypted data transmission
- Regular polling to display current device states
- Energy consumption of up to 0.23 W



Quick installation and setup




- Installation without disassembling the enclosure
- Connecting to a hub via the line scanning feature or QR code
- On-site or remote configuration and testing

<div>Compliance with standards</div> <div>EN 50131 (Grade 3) INCERT SSF NFA2P</div>	<div>Compatibility with hubs</div> <div></div> <div>For detailed information, scan the QR code or follow the link: ajax.systems/tools/devices-compatibility/?models=KP.Y.F</div>	<div>Communication with a hub</div> <div>Fibra communication technology</div> <div>Wired connection U/UTP cat.5 4×2×0.51 mm (24 AWG) cable, copper conductor 4×0.22 mm² signal cable, copper conductor</div> <div>Communication range up to 2,000 m up to 6,550 ft With U/UTP cat.5 4×2×0.51 mm (24 AWG) cable</div>	<div>Features</div> <div>Access codes keypad code personal codes for registered users codes for unregistered users RRU codes</div> <div>Duress codes keypad duress code personal duress codes</div> <div>Panic button</div>
<div>Power supply</div> <div>Fibra line 5–30 V$\overline{=}$, up to 0.23 W</div>	<div>Installation</div> <div>Operating temperature range from –10 °C to +40 °C from 14 °F to 104 °F Operating humidity up to 75%</div>	<div>Enclosure</div> <div>Color white, black</div> <div>Dimensions 150 × 103 × 19 mm 5.91" × 4.06" × 0.75"</div> <div>Weight white device: 181 g (6.38 oz) black device: 165 g (5.82 oz)</div> <div>Protection class IP50</div> <div>Impact protection IK04</div>	<div>Complete set</div> <div>Superior KeyPad Fibra SmartBracket mounting panel Installation kit Quick start guide</div>

¹ When using a U/UTP cat.5 4×2×0.51 cable.



For detailed information, scan the QR code or follow the link:
ajax.systems/support/devices/superior-keypad-fibra/

-  support@ajax.systems
-  @AjaxSystemsSupport_Bot
-  ajax.systems